

BLOCOFIX

Screenfiller

DESCRIPTION

Screenfiller for solvent based inks, high covering capacity and easy water dissolution.

RECOMMENDED APPLICATION

Manual use	Apply with a brush or a coating trough.
Solvent base ink	Excellent.
UV solvent base ink	Excellent.

CHARACTERISTICS

Colour	Blue.
Viscosity	Low.
Screen dry	Fast.

RESISTANCE

Solvent ink resistance	Excellent.
Mixed ink resistance	Not recommended.
Water based ink resistance	Not recommended.
Mechanical resistance	Excellent.

HANDLING PROPERTIES

Pot life of packing	1 year.
Screen recovery	Excellent, with water

PACKAGING

12 Kg. box	12 units x 1 Kg.
20 Kg. box	4 units x 5 Kg.

INSTRUCTIONS OF USE

Screen application

Apply with a brush or a coating trough the zone of the screen to touch-up or retouch. Before using let dry the screen completely.

Removal

When cleaning the screen will be necessary, rinse with water and the removal will be immediate.

ADDITIONAL INFORMATION

Safety data sheet is available through Kopimask or your nearer supplier.
 KOPIMASK, S.A. Tlph. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail kopimask@kopimask.es

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO 9001:2000 N°: E204216



www.kopimask.com